



VOC Data Sheet

PRODUCT	PRODUCT NAME		g/Lt	SCAQMD PRODUCT TYPE
246158	SEAL N FLEX 1 GREY	20X380GM	74	ARCHITECTURAL SEALANTS
246204	SEAL N FLEX 1 BLACK	20X380GM	74	ARCHITECTURAL SEALANTS
246220	SEAL N FLEX 1 WHITE	20X380GM	74	ARCHITECTURAL SEALANTS
216275	SEAL N FLEX 1 GREY	720GM	64	ARCHITECTURAL SEALANTS
217824	SEAL N FLEX 1 L/STONE	720GM	64	ARCHITECTURAL SEALANTS
217808	SEAL N FLEX 1 BLACK	720GM	64	ARCHITECTURAL SEALANTS
216267	SEAL N FLEX 1 WHITE	720GM	64	ARCHITECTURAL SEALANTS
217751	SEAL N FLEX 1 B/BEIGE	720GM	64	ARCHITECTURAL SEALANTS
226203	SEAL N FLEX 1 S/STONE	720GM	64	ARCHITECTURAL SEALANTS
218626	SEAL N FLEX 1 OFF WHITE	720GM	64	ARCHITECTURAL SEALANTS
232440	SEAL N FLEX 1 M/SAND	720GM	64	ARCHITECTURAL SEALANTS
242322	SEAL N FLEX 1 CLASS BONE	720GM	64	ARCHITECTURAL SEALANTS
232556	SEAL N FLEX 1 EPPING GRY	720GM	64	ARCHITECTURAL SEALANTS
226289	SEAL N FLEX 1 BRONZE	720GM	64	ARCHITECTURAL SEALANTS

1/10/14

Unless otherwise stated, the TVOC of this product has been calculated theoretically, based on the known VOC values of the individual raw material components. In the event that the VOC level of any individual raw material component is unknown, the TVOC has been determined experimentally using SCAQMD Method 304-91, as referenced by the South Coast Air Quality Management District (SCAQMD) Rule 1168.

Sugan Naidoo
Technical Director



Quality Endorsed ISO 9001 (Thomastown)
TS 16949 (Automotive)

Note:

For any further enquires contact Bostik on (03) 9279 9333 or voccertificates.australia@bostik.com. A VOC level of "0" is a true value. The VOC level of a product which may be available in a range of colours may vary depending on the colour.

Head Office: Bostik Australia Pty Ltd, 51-71 High Street, Thomastown Vic 3074
ABN 79 003 893 838
Tel: 03 9279 9333 Fax: 03 9279 9270

www.bostik.com.au

A company of TOTAL

www.bostik.com.au

Bostik Australia owns all copyright in these product instructions. All rights reserved.